

STEIN-diaphragm-wall-grab K 610 II





for the Wall thickness 600 / 800 / 1000 mm

with wire-rope-pulleys \varnothing 800 mm for wire-rope \varnothing 34 - 36 mm
one double sheave and two single sheaves

The diaphragm wall grab is low in maintenance and is subjected to the safety regulation VCB 9a for handling of loads.

The cutting edges of the grab jaws are made of Hardox steel 450 and were especially hardened. Easy mounting of the grab jaws for excavation widths 600/800/1000 mm. All the grab teeth as well as all the wire rope pulleys are quickly exchangeable due to their construction as ready to use components.

Paintwork: aluminium coloured rust protection coating.



MFS Maschinenfabrik GmbH & Co KG

Production

Phone + 49 (0) 4421 1434 0
 Fax + 49 (0) 4421 3034 81
 E-mail info@mfs-mafa.de
 Address Langeoogstr. 13
 26384 Wilhelmshaven | Germany

Sale

Phone + 49 (0) 2323 9266 0
 Fax + 49 (0) 2323 9266 25
 E-mail kendlik@stein-ht.de
 Address Schnittstr. 6
 44653 Herne | Germany

grab - body [kg]	14.200					
extension 600 - 800 mm [kg]	3.800					
light extension 600 - 800 mm [kg]	1.050					
light extension 600 - 1000 mm [kg]	2.000					
jaws opening [mm]	2800			3400		
jaws width [mm]	600	800	1000	600	800	1000
jaws weight [kg]	-	2.900	-	2.550	-	-
overall weights minimal [kg]	18.150		16.750			
overall weights maximal [kg]	21.950		20.550			

Documentation: technical specification, instruction sheet, maintenance manual, sheaving diagram, spare-parts list, safety instructions.