

STEIN-diaphragm-wall-grab K 810





for the wall thickness 800 / 1000 / 1200 mm

with wire-rope-pulleys \varnothing 600 mm for wire-rope \varnothing 28 - 32 mm
two double sheaves and one single sheave

The diaphragm wall grab is low in maintenance and is subjected to the safety regulation VCB 9a for handling of loads.

The cutting edges of the grab jaws are made of Hardox steel 450 and were especially hardened. Easy mounting of the grab jaws for excavation widths 800/1000/1200 mm. All the grab teeth as well as all the wire rope pulleys are quickly exchangeable due to their construction as ready to use components.

Paintwork: aluminium coloured rust protection coating.



MFS Maschinenfabrik GmbH & Co KG

Production

Phone + 49 (0) 4421 1434 0
 Fax + 49 (0) 4421 3034 81
 E-mail info@mfs-mafa.de
 Address Langeoogstr. 13
 26384 Wilhelmshaven | Germany

Sale

Phone + 49 (0) 2323 9266 0
 Fax + 49 (0) 2323 9266 25
 E-mail kendlik@stein-ht.de
 Address Schnittstr. 6
 44653 Herne | Germany

grab - body [kg]	11.800					
extension 800 - 1000 mm [kg]	3.800					
light extension 800 - 1000 mm [kg]	1.050					
light extension 800 - 1200 mm [kg]	2.000					
jaws opening [mm]	2800			3400		
jaws width [mm]	800	1000	1200	800	1000	1200
jaws weight [kg]	2.400	3.300	4.000	2.900	3.600	4.300
overall weights minimal [kg]	14.200	16.150	17.800	14.700	16.450	18.100
overall weights maximal [kg]	18.000	19.950	21.600	18.500	20.250	21.900

Documentation: technical specification, instruction sheet, maintenance manual, sheaving diagram, spare-parts list, safety instructions.